

MX MARINE HOIST DETAILS

ADDITIONAL STANDARD FEATURES:

- ALL HYDRAULIC CONTROL
- FOUR HOIST LIFTING PRECISION AT THE OPERATOR'S FINGERTIPS, WITH ADDITIONAL GROUND LEVEL REMOTE CONTROLS FOR WINCH AND ENGINE THROTTLE
- TWO-WHEEL "TORSION-TRAC" PLANETARY DRIVE SYSTEM WITH AUTOMATIC HOLDING BRAKE AND ADDITIONAL HYDRAULIC DRIVING BRAKE PACKAGE
- DURABLE POLYESTER LIFTING SLINGS FOR LESS STRETCH WHILE HAULING
- TRAVEL ALARM
- SIGHT GAUGES ON FUEL AND OIL TANKS
- GALVANIZED LIFTING CABLES
- NON-SKID OPERATOR'S PLATFORM WITH GUARD RAIL CENTRALLY-LOCATED FOR THE BEST "BIRD'S EYE" VANTAGE POINT OF ALL OPERATIONS AND RIGGING
- ALL STAINLESS STEEL HYDRAULIC LINES AND SLING LIFTING PINS
- ZERC FITTINGS ON THE END OF ALL SHEAVE MOUNTING PINS FOR EASE OF MAINTENANCE
- POWERED SLING ADJUSTMENT FOR 50 TONS AND UP (BOTH FORE AND AFT SLING SETS)

OPTIONS:

- WIRELESS LOAD WEIGHT INDICATOR SYSTEM
- HEAVY LUG TREADED TIRES
- 12V SAFETY, TRAVEL AND WORK LIGHTING PACKAGES
- ADDITIONAL LIFT CABLE FOR GREATER SLING DROP BELOW GRADE
- BOLTED FLANGE PLATE IN CROSSBEAM FOR SIMPLIFIED FUTURE FRAME WIDENING
- AUXILIARY JIB BOOM
- POWERED SLING ADJUSTMENT AVAILABLE FOR ALL MODELS (BOTH FORE AND AFT SLING SETS)
- "UNDER SLUNG" ENGINE MOUNTING BELOW THE MAIN POWER HEAD BEAM
- STEEL ROOF FOR OPERATOR PLATFORM OR FULLY ENCLOSED CAB
- BIO-DEGRADABLE HYDRAULIC OIL
- CUSTOMIZABLE FRAME DIMENSIONS AND COMPONENT CONFIGURATIONS TO SUIT CUSTOMER NEEDS